## Check the LPG Tank before Buying

Always look for the DOE-required weighing scale at LPG stores or outlets.

#### To determine the net content of LPG:

- (1) Look for the tare weight (weight of the empty tank) of the LPG you're buying. TW is indicated on the tank's shoulder.
- (2) Weigh the filled LPG tank.
- (3) Deduct the tare weight from the weight of the filled LPG tank.

## Example:

Weight of Filled LPG Tank 24.0 kg Tare Weight (TW)\* 13.0 kg

11.0 kg Correct Net Content



\*weight varies among different suppliers/dealers

# Quick Facts on LPG


Liquified Petroleum Gas (LPG) is a mixture of 60% butane and 40% propane. It is derived from the distillation of crude oil in the refining process — in the same manner that other liquid fuels such as kerosene, gasoline and diesel are extracted.



### Contact us:

Consumer Welfare and Promotion Office Department of Energy G/F DOE Annex Building, Rizal Drive cor. 34th Street, Bonifacio Global City, Taguig Telephone: (02) 479-2900 Loc 329 Telefax: (02) 840-2267

Mobile (Globe): 0917-556-0759 Website: www.doe.gov.ph



## Consumer Welfare and **Promotion Office**

**Empowering Energy Consumers** 



Pure LPG is odorless.

safety purposes, chemical odorant called Ethyl Mercaptan is added so any leak can be detected by scent.

Pure LPG is colorless. It is clear as water in liquid form.



LPG is not poisonous when inhaled and is environment-friendly because emits less carbon dioxide.



can cause natural rubber and some plastics to deteriorate.

Keep LPG cylinders away from electrical points and other sources of fire/ ignition.



Do not invert LPG cylinders or let them lie horizontally on






the floor.

LPG-resistant Use only rubber hoses with clamps and regularly check for wear, cracks and leaks using soapy water.



not store cylinders in enclosed kitchen cabinets.






Look for a weighing scale when buying an LPG.



Buy LPG cylinders with Tare Weight (TW) markings.





# What to do when there is a leak?



Open all doors and windows to improve ventilation.



Do not switch on/off electrical switches or connect/disconnect electrical plugs.



If the leak is in the cylinder, move the cylinder out to an open and well-ventilated place.

Seek help from the retail outlet where LPG was purchased or call the proper authorities.